



**TGM 15.250 4X2 BL CH CC**



# TGM 15.250 4X2 BL CH CC

## CABIN

- MAN compact size day cabin with synthetic bumper
- Coil spring cab mounts and air suspended driver's seat for high productivity and well-being of driver
- LED daytime running lights
- Multi-function 4-spoke steering wheel with adjustable height inclination angle and parking position
- MMT radio with 7" display and Bluetooth®

## ENGINE

- MAN D0836LFL89 Euro 5 exhaust emission norm, in-line 6 cylinder engine with high output common rail injection system
- 6891 ccm displacement; ; 250hp /184 kW at 2200 rpm, 1050Nm at 1200 – 1600rpm
- Air compressor 1-cylinder, 238 ccm

## AIR INTAKE SYTEM

- Hybrid MAN air-intake system located behind the cab
- The intake duct for the engine air intake equipped with an additional pre-separator
- Safety insert inside the filter

## TRANSMISSION

- MAN TipMatic® 12 12 OD (overdrive) automated manual gearbox  
Twelve forward gears:  
1st gear 10.37:1  
12th gear 0.81:1  
Two reverse gears
- Gearbox features include Smartshifting, idle speed driving, slope and load detection

## FRONT AXLE & SUSPENSION

- MAN VOK-07 dropped, 6.3t capacity
- 2-leaf parabolic springs 6.3t enabling high frontal ground clearance
- Stabilizer and shock absorbers

## REAR AXLE & SUSPENSION

- 11t robust MAN Hypoid rear axle with a final drive ratio  $i=4.11$
- Air suspension 10t
- Stabilizer and shock absorbers on rear axle

## RIMS & TYRES

- Front: 305/70R19.5 tyres, with 8-hole 8.25 x 19.5 steel rims
- Rear: 305/70R19.5 tyres, with 8-hole 8.25 x 19.5 steel rims

## BRAKING SYSTEMS

- MAN BrakeMatic® system for control of continuous brakes with Bremsomat functions
- High-performance engine brake
- Disc brakes all-round with anti-lock brake system (ABS)

## ELECTRICAL SYSTEMS

- System Voltage 24V; 2x 12V 88Ah batteries
- Basic alternator 28V 110A 3080W

## CHASSIS FRAME & ATTACHMENTS

- U section main members of high strength TM500 tempered steel with riveted & bolted cross members, profile 270 x 70 x 6.8 mm
- Steel fuel tank 300L on right
- AdBlue tank 35L right

## SAFETY & DRIVER ASSISTANCE FEATURES

- MAN EasyStart for TipMatic® (Hill Start Assist)
- Electronic Stability Control (ESP) with functions of dynamic stability (DSP) and rollover prevention (ROP)
- Anti-Slip Control (ASR)

## DIMENSIONS & MASS DATA

L x W x H (mm)	9900x 2454 x 2709 mm
Wheelbase	5475 mm
Front overhang	1350 mm
Rear overhang	3075 mm

GVM	15 000 kg
GCM	28 000 kg
GA Front	6 300 kg
GAU Rear	10 000 kg

**NOTE:** The manufacturer reserves the right to make changes to the design, form, colour and specification during the delivery period. Please consult your MAN sales executive to confirm final specifications upon ordering.

**MAN Automotive (South Africa) Proprietary Limited – A member of the MAN Group**  
Founders Hill Office Park, The Views, 18 Centenary Way, Founders Hill, Modderfontein 1609 South Africa

Tel: +27 11 928-6800 ■ [www.mantruckandbus.co.za](http://www.mantruckandbus.co.za)

